


2-PC BALL VALVE (Full bore)

二片式球阀（通径）




MV-22C

- 螺纹标准: ISO, BS, DIN, JIS, ASME
- 公称压力: 2000 PSI (PN125)
- 工作温度: $-25^{\circ}\text{C} \sim +180^{\circ}\text{C}$
- 材 料: CF8M, CF8, CF3M, WCB
- Investment casting for body and cap
- Full bore
- Thread: ISO, BS, DIN, JIS, ASME
- Pressure rating: 2000 PSI (PN125)
- Working temperature: $-25^{\circ}\text{C} \sim +180^{\circ}\text{C}$
- Material: CF8M, CF8, CF3M, WCB

MATERIAL LIST

ITEM	PART	MATERIAL	QTY.
1	Body	CF8M	1
2	Ball Seat	R-PTFE(15%)	2
3	Ball	SS316	1
4	Body Gasket	PTFE	1
5	Cap	CF8M	1
6	Stem	SS316	1
7	Thrust Washer	PTFE	1
8	Stem Packing	PTFE	1
9	Gland Nut	SS304	1
10	Handle	SS304	1
11	Spring Washer	SS304	1
12	Nut	SS304	1
13	Lock Device	SS304	1
14	Handle Cover	PLASTIC	1

PRESSURE-TEMPERATURE RATING



DIMENSION LIST

SIZE	d	L	H	W	N-m	Kgs
1/4"	11.5	49	54	105	4	0.23
3/8"	12.5	49	54	105	4	0.23
1/2"	15	58	56	105	5	0.31
3/4"	20	65	65	118	8	0.55
1"	25	77	70	150	10	0.74
1-1/4"	32	90	75	150	14	1.21
1-1/2"	40	105	93	182	18	1.86
2"	50	125	99	182	25	2.97