



MV-33S

3-pc Socket Weld Ball Valve

- Investment casting for body and cap
- Full bore
- Socket weld: BS EN12760-1999
- Length: DIN3202-M3
- Pressure rating: 1000 PSI (PN63)
- Working temperature: -25°C +180°C
- Material: CF8M, CF8, CF3M, WCB
- 精密铸造三片式承插焊球阀 (口径)
- 承插焊标准: BS EN12760-1999
- 长度标准: DIN3202-M3
- 公称压力: 1000 PSI(PN63)
- 工作温度: -25°C +180°C
- 材 料: CF8M, CF8, CF3M, WCB

DIMENSION LIST

SIZE	d	D	P	L	H	W	N • m	Kgs
1/4"	11	14	10	50	51	105	4	0.38
3/8"	12.5	17.6	10	60	51	105	4	0.40
1/2"	15	21.7	10	75	53	118	5	0.41
3/4"	20	27.3	13	80	60	118	8	0.71
1"	25	34.1	13	90	75	150	10	0.95
1-1/4"	32	42.8	13	110	80	150	14	1.64
1-1/2"	40	48.7	13	120	88	182	18	2.36
2"	50	61.1	16	140	95	182	25	3.42
2-1/2"	65	77	16	185	121	254	48	6.88
3"	80	90	16	205	135	254	75	11.50
4"	100	115.2	20	240	158	285	110	19.90